


ICEFIRE-ET

Enterprise Tablet PC

- 10.4" TFT 350 cd/m² XGA LCD with multi resistive touch
- Intel® Atom™ D525 dual core platform
- Powered by Windows® Embedded Standard 7 P
- 3 Megapixels camera with LED flash
- Bluetooth, Wi-Fi, Ethernet LAN
- Dual hot swappable batteries
- Optional docking station / smart card reader



Applications



Enterprise Mobility

Using technology to quickly move products helps save your time and increases productivity. The right technology enables the flow of information between handheld devices used by your workers and your core business systems. The ICEFIRE-ET utilizes wireless local area networks (WLANs) and management software to increase the data transfer speed and optimize your working mobility in logistics and warehousing environments.

Inspection

The ICEFIRE-ET is most suitable for inspection applications. It features an ergonomic and light weight design that is easy to carry around on-the-job. It also offers exceptional functions that allow information to be stored in real-time and help businesses to provide transparent inspection and accurate information.



Logistics and Warehouse

Enhancing on-duty staff work force and mobility, the tablet PC brings more efficiency to the workplace. All data and information are saved in the ICEFIRE-ET and can be transferred via wireless communication providing real-time responses without any loss.

1
iE Mobile
Solutions

2
Automation
Panel
Solutions

3
RISC-
based
Solutions

4
PACSmate
Medical
Solutions

5
Optional
Peripherals



Specifications

Model	ICEFIRE-ET	
Display	LCD Size	10.4" TFT LCD
	Brightness (cd/m ²)	350 cd/m ²
	Max Resolution	1024 x 768 pixels XGA
	Viewing Angle	88/88/88/88 Deg.
	Touch Screen	Resistive Support Multi-touch and Gesture
System	CPU	Intel® Atom™ D525 1.8GHz
	Chipset	Intel® ICH8M
	Operating System	Microsoft® Windows® Embedded Standard 7 P
	Memory	2GB DDR3 SDRAM 1333MHz
	Storage	1.8" SSD, SATA
Communication	Wireless LAN	Wi-Fi 802.11a/b/g/n
	Bluetooth	Bluetooth V2.1+ EDR (Class II)
Data Collection	Camera	3 megapixels and LED Light
Indicators & Buttons	LED Indicators	Power/ Wi-Fi/Bluetooth/ Battery Status LED
	Keys	5-way Navigation Key Camera/Wi-Fi/Bluetooth/SAS/Function Key
I/O Interface	USB	1 x USB 2.0 FULL SPEED
	LAN	1 x 10/100M LAN
	Audio	1 x 2W Speaker
		1 x Mic in
Power	Power Adapter	12V@5A@60W
	Docking Power Adapter	19V@4.74A@90W
	Battery	11.1V 1880mAh Li-ion Battery
Environment	Operating Temperature	0°C to +40°C
	Storage Temperature	-10°C to +60°C
	Humidity	5%~95% non-condensing
	Drop Survival	1.0 M
	Environmental Protection	IP 64 compliant front panel compliant
	Certification	UL/CE/FCC
Physical Characteristics	Dimensions (LxWxH) (mm)	270 x 265 x 29
	Weight	1788g

1
IEIMobile Solutions

2
Automation Panel Solutions

3
RISC-based Solutions

4
PACSmate Medical Solutions

5
Optional Peripherals

Ordering Information

With SSD&OS

Part No.	Description
ICEFIRE-T10A-ET/2G-32S-R10	10.4" TFT-LCD 350 cd/m ² XGA Industrial Mobile Clinical Assistant with Dual-core 1.8GHz Intel® Atom™ D525 CPU, Integrated Resistive Touch, 2GB DDR3 RAM, 802.11a/b/g/n Wireless, Bluetooth, 3M Pixels Camera, 32G SSD, WS7P, RoHS

Packing List

Item	Part No.
Stylus	XTR104-0002-RS
Battery Pack-B	31603-000020-RS
Non-Medical-grade Power Adapter (12V/60W)	63000-FSP060DBAB1553-RS
User's Manual CD ROM	7B000-000552-RS

Dimensions (Unit: mm)

