

ODP 333 from AURES: Soon available in white

Lisses - Fürstenfeldbruck - 26. December 2013. *The new generation **ODP 333** receipt printer from the **AURES** Group has dressed itself up in white for New Year celebrations; the pure white lacquered surface, with mirrored reflections, enhances its contemporary look, in perfect harmony with the style of the latest generation of AURES EPOS terminals.*

- The ODP 333 is very compact compared to traditional EPOS receipt printers. It features a cubic design with elegant *black* or *white* matt and gloss finish.
- It has a very ergonomic, splash-proof front receipt print-out, providing optimal protection against dust, crumbs and splashes in tough settings (*kitchens, restaurants, cafés, baker's shops, etc.*).
- The ODP 333's low energy consumption motherboard (*Energy Star certified*) switches it to standby mode as soon as it is no longer in use. This guarantees reduced electricity consumption – *an average of 30% less* – in line with new environmental standards for green technology.

The ODP 333 printer will be available in white from early 2014.

The ODP 333's plus points

- EPOS printer with contemporary cubic design (very ergonomic format)
- Low energy consumption motherboard (*consumes less electricity*)
- Triple interface: RS-232-C,, USB and Ethernet
- Front receipt print-out - for a splash-proof, more watertight design, especially in tough café, hotel and restaurant settings.
- Print speed: 160 mm/sec
- Configuration utility
- All cables supplied
- Integrated buzzer
- Available in black or white

(See the full technical data sheet below)



About the AURES Group

Founded in 1989 and listed on Euronext since 1999, **AURES** manufactures electronic points of sale terminals and systems – together with related peripherals. This PC-based, open-system (*EPOS hardware*) is designed to provide management and till functions in specialist food and non-food stores, retail outlets, superstores or the catering and hospitality industry - and all other points of sale and service.

The **AURES Group** - which includes **AURES Technologies** and **J2 Retail Systems** - has global presence, with its head office in France, subsidiaries in Great Britain, Germany, Australia and the USA - and a network of distributors and resellers located in more than 50 other countries.

In 2013, the **AURES** Group represents over 50,000 deployed systems and sales in excess of €50 million.

For additional information, please contact:

Yannick-Florence WAELLY

+33(0)1 69 11 16 65 (LD)

yannick.waelly@aures.com

www.aures.com



The **sango** Pack with white ODP 333 receipt printer

(Photos AURES 2013)

ODP 333 - Technical features

| | |
|------------------------------|---|
| <u>Print method</u> | <u>direct, thermal</u> |
| <u>Print speed</u> | <u>160mm/sec</u> |
| <u>Effective Print Width</u> | <u>72mm / 512 dots/line</u> |
| <u>Characters per line</u> | <u>Font A: 42 columns, 180dpi</u> <u>Font B : 56 columns, 180dpi / 64 columns, 203dpi</u> |
| <u>Internal memory</u> | <u>64MB</u> |
| <u>Motherboard</u> | <u>low power consumption – automatic standby mode</u> <u>enables 30% less power use on average</u> |
| <u>Paper loading</u> | <u>automatic</u> |

Thermal paper

| | |
|---------------------------|-------------------------|
| <u>Width</u> | <u>79.5mm +/- 0.5mm</u> |
| <u>Thickness</u> | <u>0.065 – 0.1mm</u> |
| <u>Max. roll diameter</u> | <u>83mm</u> |

Characters

| | |
|---------------------------------|--|
| <u>Alphanumeric</u> | <u>95</u> |
| <u>Extended graphic</u> | <u>128 x 18 pages</u> |
| <u>International characters</u> | <u>14</u> |
| <u>Barcode</u> | <u>UPC - A, UPC-E, EAN-8, Code 39, Code 93, Code 128, ITF,</u> <u>Codabar, 2D PDF417, QR Code</u> |
| <u>Emulation</u> | <u>ESC/POS compatible</u> |
| <u>Drivers</u> | <u>Windows (XP, 2000, 2003, Vista, WEPOS) / OPOS / Linux / Java POS</u> |
| <u>Sensor</u> | <u>end-of-roll, near end-of-roll, cover open</u> |
| <u>Till output port(s)</u> | <u>1 dual port (for 2 drawers) - RJ11 6-pin connector</u> |
| <u>Interfaces</u> | <u>Triple interface</u> <u>RS232 Serial - USB & Ethernet dual (non-modifiable)</u> |
| <u>Power supply</u> | <u>External 24V - 1,75A</u> |
| <u>Integrated buzzer</u> | |

Paper cutter

| | |
|--------------------|--|
| <u>Auto cutter</u> | <u>guillotine type</u> <u>Max. 30 cuts/minute</u> |
| <u>Cut type</u> | <u>total or partial</u> |

Other features

| | |
|--|--|
| <u>MCBF</u> | <u>35-50 million lines depending on type of use and paper thickness</u> <u>Printer head lifespan: 160km</u> <u>Paper cutter lifespan: Approx. 1.5 million cuts</u> |
| <u>Operating temperature</u> | <u>-20 to +60°C</u> |
| <u>Operating humidity</u> | <u>10% to 90% (without condensation)</u> |
| <u>Dimensions (depth x width x height)</u> | <u>165 x 135 x 105.02mm</u> |
| <u>Weight</u> | <u>1kg approximately</u> |
| <u>Colours</u> | <u>Black or White</u> |