

For Immediate Release

## TAIYO YUDEN Develops Automotive SMD Power Inductors with an Operating Temperature of up to 150°C

*Optimum for powertrain components, focusing on traceability*



TOKYO, March 27, 2017—TAIYO YUDEN CO., LTD. has announced today the development and production of the AEC-Q200-compliant SMD power inductor EST1060 (10.1 x 10.0 x 6.0 mm).

This product is a power inductor for choke coils and filters in DC-DC converters, which are power supply circuits used in automotive powertrain components such as engines and transmissions.

By making full use of our material technology, we have extended the upper limit of the operating temperature range to 150°C (including self-generated heat); and by utilizing our own structural design, we have achieved a vibration resistance of 30G (under our test conditions). Furthermore, a unique Data Matrix Barcode is printed on each unit which allows traceability throughout all processes such as production and distribution.

Shipment of product samples will start in March 2017, and commercial production will start at FUKUSHIMA TAIYO YUDEN CO., LTD. (Date-City, Fukushima Prefecture, Japan) in August 2017. The sample price is 80 yen per unit.

### Technology Background

Vehicles produced recently are equipped with a greater number of electronic control units (ECUs) such as ADAS, which require more power supply circuits. This has resulted in increasing demands for power inductors used in such circuits. In particular, since more ECUs are installed in the engine room, subject to high temperatures, electronic components used in the ECUs must possess high heat and vibration resistance.

TAIYO YUDEN has adopted our optimized material technology and structural design into the power inductor, which achieves a heat resistance of 150°C and a mechanical strength against 30G vibrations. Furthermore, we are promoting visualization of the manufacturing processes to strengthen quality control. As part of this activity, we print a unique Data Matrix Barcode on the product, piece by piece, to trace each unit throughout all manufacturing processes.

TAIYO YUDEN focuses on the product development of SMD power inductors in order to meet market demands, and will continue to expand their line-up to 6, 7, and 12 mm square sizes.

■ Applications

Choke coils for automotive powertrain components such as engines and transmissions

■ Characteristics of the metal wire-wound chip power inductor MCOIL™ MC series released on this occasion are shown below.

Product name	Inductance [μH]	Inductance allowance	DC resistance [mΩ] max.	Rated current [A] max.	
				DC saturation allowable current	Temperature rise allowable current
EST1060T100MDGA	10	±20%	22	5.2	4.9
EST1060T150MDGA	15		31	4.4	4.1
EST1060T220MDGA	22		44	3.6	3.4
EST1060T330MDGA	33		61	3.1	2.9
EST1060T470MDGA	47		84	2.35	2.5
EST1060T680MDGA	68		108	2.05	2.2
EST1060T101MDGA	100		169	1.65	1.75
EST1060T151MDGA	150		246	1.35	1.45
EST1060T221MDGA	220		350	1.15	1.2
EST1060T331MDGA	330		460	0.9	1.05
EST1060T471MDGA	470		775	0.75	0.8

Note: The products are tested based on the test conditions and methods defined in AEC-Q200. Please consult with TAIYO YUDEN for the details of the product specification and AEC-Q200 test results, etc., and please review and approve TAIYO YUDEN's product specification before ordering.

TAIYO YUDEN CO., LTD. Product Inquiries <http://www.yuden.co.jp/or/contact/>

[http://www.taiyo-yuden.com/images/stories/taiyo/pdf/EST\\_1060\\_Mar17.pdf](http://www.taiyo-yuden.com/images/stories/taiyo/pdf/EST_1060_Mar17.pdf)