

# True Flat Medical All-in-One PCs G Series

Medical

Product Sheet



Front view



Rear view with removed cable cover and cooling plate with VESA mounting holes

## Key Features

21.5" 24"



Full HD resolution and also available as a display version without PC



True Flat design with AR protection glass and IP54 housing



Optional with PCap Touch, operable by finger or gloves



Medical certified (DICOM<sup>®</sup> compliant)



Long-term available with plastic housing and Front Touch Keys



High performance 6<sup>th</sup> Gen. Intel<sup>®</sup> Core™ i5-6300U CPU and Intel<sup>®</sup> HD Graphics 520



Many additional features: WLAN/Bluetooth, RFID/NFC, Webcam, ...



Individually configurable through customizing

# True Flat Medical All-in-One PCs

## G Series

### Technical Specifications

21.5"

24"

Model	21.5" Medical Display		24" Medical Display		PC Specifications	
Size	21.5" / 54.6 cm		23.8" / 60.5 cm		CPU	
Aspect Ratio	16:9				6 <sup>th</sup> Gen. Intel® Core™ i5-6300U, 2 Core, 2.4 GHz	
Active Area (H x V)	476.6 x 268.1 mm		527.0 x 296.4 mm		Memory	
Resolution	1920 x 1080 / Full-HD				8 GB (up to 16 GB) DDR4 2133 SDRAM	
Pixel Pitch	0.248 mm		0.2745 mm		Graphics	
Display Colors	16.7 M				Intel® HD Graphics 520	
Response Time	18 ms		12 ms		Supported OS	
Brightness	250 cd/m <sup>2</sup> typ.				Windows 7 / 8 / 8.1 / 10 Linux	
Contrast Ratio	3000:1 typ.				HDD	
Viewing Angle (H x V)	178° / 178°				2.5" SATA3 128 GB SSD (optional 256 GB SSD)	
Temperature Operating	0 °C to +40 °C	+32 °F to +104 °F	0 °C to +40 °C	+32 °F to +104 °F	I/O Ports	
Humidity Operating	0 % to 90 % RH				Serial	
Power Consumption	~ 30 W		~ 35 W		1x RS-232 / 422 / 485 1x RS-232	
Power Supply	External 24 VDC				USB	
Dimensions (W x H x D)	521.0 x 326.0 x 56.5 mm	20.5 x 12.8 x 2.2 in	587.0 x 367.5 x 59.5 mm	23.1 x 14.5 x 2.3 in	4x USB 3.0	
Weight	6.7 kg	14.8 lbs	7.6 kg	16.8 lbs	Audio	
Safety & Ergonomics	CE (IEC/EN60601-1: ed. 3.1, IEC/EN60601-1-2:2014/2015, 4 <sup>th</sup> ed.), cUL (ANSI/AAMI ES60601-1:2005+A1, CAN/CSA C22.2 NO.60601-1:14), FCC				Speakers 2x 2 W, Audio out and Mic in	
Misc.	True Flat design with AR protection glass and IP54 (without I/Os), Front Touch Keys, fanless, white plastic housing (RAL 9003), LED backlight				Equipotential Pin	
Options	PCap (Projected Capacitive Touch), WLAN/Bluetooth, RFID/NFC, Webcam, Reading lights, Backup-Battery				yes	
Options Customizing	Other PC configurations, interfaces, branding, housing color, OS, ...				LAN	
					Optional Upgrade Module	
					Serial	
					1x RS-232 / 422 / 485 (isolated 5 kV) 1x RS-232 (isolated 5 kV)	
					USB	
					2x USB 2.0 (isolated 5 kV)	
					LAN	
					2x Gigabit Ethernet (isolated 5 kV)	
					HDMI	
					1x HDMI out	

### Different Views



Illustration of the I/Os

Front Touch Keys

